

60W Solar LED Flood Light Quotation



Main Features:

1. IP65 waterproof;
2. Charging and discharging indicator light: 25%, 50%, 75%, 100%;
3. Easy to install it on the wall or pole with the 180 degree adjustable install bracket;
4. 5M waterproof connect cables: make it possible to use in indoor(warehouse or garage);
5. Support remote control with 3 main functions: a). brightness \pm from 10% to 100%; b). 3H, 5H, or 8H timer for choosing; c). red and blue indicator light cool flashing or constant lighting.

Package	Qty/Carton (PCS)	6PCS/ Carton	N. W.: (KG)	18.8KGs
	Carton Size (MM)	710(L)*360(W)*435(H) MM	G. W.: (KG)	20.5KGs

LED Power(W)	60W
LED Quantity(PCS)	108PCS SMD2835 LED Chip
LED Color Temperature(K)	6,000K - 6,500K
Solar Panel(W)	12W, 6V
LiFePO4 Battery Capacity(MAH)	12,000MAH, 3.2V
Charging Time(H)	6 - 8 Hours by Bright Sunlight
Discharging Time(H)	>3 Nights after LiFePO4 Battery is Fully Charged
Charging and Discharging Indicator Light	4 Indicator Lights: 25%, 50%, 75%, 100%
Connect Cable Length(M)	5M Waterproof Connect Cable
Main Material	Die-casting Aluminum + PC
Solar Panel Size(MM)	370(L)*305(W)*17(H)MM
LED Flood Lamp Size(MM)	220(L)*175(W)*60(H)MM
Waterproof Grade	IP65
Working Temperature($^{\circ}$ C)	(-)25 $^{\circ}$ C ~ 60 $^{\circ}$ C
Warranty	3 Years
Lighting Mode	Light Sensor(turn on at night and off at day automatically) + Remote Control by a Controller(functions: 1. brightness \pm from 10% to 100%; 2. timer 3H, 5H, 8H for choosing; 3. red and blue indicator light cool flashing or constant lighting)

100W Solar LED Flood Light Quotation



Main Features:

1. IP65 waterproof;
2. Charging and discharging indicator light: 25%, 50%, 75%, 100%;
3. Easy to install it on the wall or pole with the 180 degree adjustable install bracket;
4. 5M waterproof connect cables: make it possible to use in indoor(warehouse or garage);
5. Support remote control with 3 main functions: a). brightness \pm from 10% to 100%; b). 3H, 5H, or 8H timer for choosing; c). red and blue indicator light cool flashing or constant lighting.

Package	Qty/Carton (PCS)	5PCS/ Carton	N. W.: (KG)	22.8KGs
	Carton Size (MM)	600(L)*426(W)*485(H) MM	G. W.: (KG)	24.5KGs

LED Power(W)	100W
LED Quantity(PCS)	176PCS SMD2835 LED Chip
LED Color Temperature(K)	6,000K - 6,500K
Solar Panel(W)	18W, 6V
LiFePO4 Battery Capacity(MAH)	18,000MAH, 3.2V
Charging Time(H)	6 - 8 Hours by Bright Sunlight
Discharging Time(H)	>3 Nights after LiFePO4 Battery is Fully Charged
Charging and Discharging Indicator Light	4 Indicator Lights: 25%, 50%, 75%, 100%
Connect Cable Length(M)	5M Waterproof Connect Cable
Main Material	Die-casting Aluminum + PC
Solar Panel Size(MM)	420(L)*370(W)*17(H)MM
LED Flood Lamp Size(MM)	265(L)*210(W)*60(H)MM
Waterproof Grade	IP65
Working Temperature($^{\circ}$ C)	(-)25 $^{\circ}$ C ~ 60 $^{\circ}$ C
Warranty	3 Years
Lighting Mode	Light Sensor(turn on at night and off at day automatically) + Remote Control by a Controller(functions: 1. brightness \pm from 10% to 100%; 2. timer 3H, 5H, 8H for choosing; 3. red and blue indicator light cool flashing or constant lighting)

200W Solar LED Flood Light Quotation



Main Features:

1. IP65 waterproof;
2. Charging and discharging indicator light: 25%, 50%, 75%, 100%;
3. Easy to install it on the wall or pole with the 180 degree adjustable install bracket;
4. 5M waterproof connect cables: make it possible to use in indoor(warehouse or garage);
5. Support remote control with 3 main functions: a). brightness \pm from 10% to 100%; b). 3H, 5H, or 8H timer for choosing; c). red and blue indicator light cool flashing or constant lighting.

Package	Qty/Carton (PCS)	4PCS/Carton	N. W.: (KG)	20.8KGs
	Carton Size (MM)	595(L)*480(W)*405(H)MM	G.W.: (KG)	22.5KGs

LED Power(W)	200W			
LED Quantity(PCS)	216PCS SMD2835 LED Chip			
LED Color Temperature(K)	6,000K - 6,500K			
Solar Panel(W)	25W, 6V			
LiFePO4 Battery Capacity(MAH)	24,000MAH, 3.2V			
Charging Time(H)	6 - 8 Hours by Bright Sunlight			
Discharging Time(H)	>3 Nights after LiFePO4 Battery is Fully Charged			
Charging and Discharging Indicator Light	4 Indicator Lights: 25%, 50%, 75%, 100%			
Connect Cable Length(M)	5M Waterproof Connect Cable			
Main Material	Die-casting Aluminum + PC			
Solar Panel Size(MM)	530(L)*350(W)*17(H)MM			
LED Flood Lamp Size(MM)	285(L)*230(W)*60(H)MM			
Waterproof Grade	IP65			
Working Temperature($^{\circ}$ C)	(-)25 $^{\circ}$ C ~ 60 $^{\circ}$ C			
Warranty	3 Years			
Lighting Mode	Light Sensor(turn on at night and off at day automatically) + Remote Control by a Controller(functions: 1. brightness \pm from 10% to 100%; 2. timer 3H, 5H, 8H for choosing; 3. red and blue indicator light cool flashing or constant lighting)			

300W Solar LED Flood Light Quotation



Main Features:

1. IP65 waterproof;
2. Charging and discharging indicator light: 25%, 50%, 75%, 100%;
3. Easy to install it on the wall or pole with the 180 degree adjustable install bracket;
4. 5M waterproof connect cables: make it possible to use in indoor(warehouse or garage);
5. Support remote control with 3 main functions: a). brightness \pm from 10% to 100%; b). 3H, 5H, or 8H timer for choosing; c). red and blue indicator light cool flashing or constant lighting.

Package	Qty/Carton (PCS)	4PCS/Carton	N. W.: (KG)	24.5KGs
	Carton Size (MM)	725(L)*520(W)*415(H) MM	G. W.: (KG)	26.2KGs

LED Power(W)	300W
LED Quantity(PCS)	360PCS SMD2835 LED Chip
LED Color Temperature(K)	6,000K - 6,500K
Solar Panel(W)	30W, 6V
LiFePO4 Battery Capacity(MAH)	30,000MAH, 3.2V
Charging Time(H)	6 - 8 Hours by Bright Sunlight
Discharging Time(H)	>3 Nights after LiFePO4 Battery is Fully Charged
Charging and Discharging Indicator Light	4 Indicator Lights: 25%, 50%, 75%, 100%
Connect Cable Length(M)	5M Waterproof Connect Cable
Main Material	Die-casting Aluminum + PC
Solar Panel Size(MM)	600(L)*350(W)*17(H)MM
LED Flood Lamp Size(MM)	350(L)*285(W)*70(H)MM
Waterproof Grade	IP65
Working Temperature($^{\circ}$ C)	(-) 25° C ~ 60° C
Warranty	3 Years
Lighting Mode	Light Sensor(turn on at night and off at day automatically) + Remote Control by a Controller(functions: 1. brightness \pm from 10% to 100%; 2. timer 3H, 5H, 8H for choosing; 3. red and blue indicator light cool flashing or constant lighting)